

# noc-activator.conf

Activator configuration

## [main] section

Name	Type	Description
logfile	String	Log file path
loglevel	String	logging level. One of: debug, info, warning, error, critical
logsize	Integer	Maximum log file size in bytes. 0 (default) means unlimited size
syslog_host	String	Syslog destination for logs
logfiles	Integer	Keep <i>logfiles</i> backup copies of log file
pidfile	String	Pid file path

## [activator] section

Name	Type	Description	Values
name	String	Activator name used for authentication	
listen_instance	String	Restrict SNMP and SYSLOG collectors to particular activator instance	0
ping_instance	String	Restrict ping checks to particular activator instance	0
ping_interval	Integer	Ping each host every <i>ping_interval</i> seconds	60
listen_traps	String	A list of addresses/ports to listen for SNMP Traps. List elements are separated by commas.	<ul style="list-style-type: none"><li>• ip</li><li>• ip:port</li><li>• interface</li><li>• interface:port</li></ul>
listen_syslog	String	A list of addresses/ports to listen for Syslog. List elements are separated by commas.	<ul style="list-style-type: none"><li>• ip</li><li>• ip:port</li><li>• interface</li><li>• interface:port</li></ul>
secret	String	Secret key used for digest authentication	
software_update	String		<ul style="list-style-type: none"><li>• <b>true</b> - enable software update on connect.</li><li>• <b>false</b> - do not update software on connect</li></ul>
max_scripts	Integer	Maximum concurrent scripts per activator	

## [sae] section

Name	Value	Description
host	<i>String</i>	Address to be used to connect SAE.
port	<i>Integer</i>	SAE port
local_address	<i>String</i>	Use specified address as source address for SAE connections. Leave empty to use default address.

## [ssh] section

SSH client related configuration

Name	Value	Description
key	<i>String</i>	Path to SSH private key. Public key must reside in <code>_key_.pub</code> file